

# MD Series




### CHARACTERISTICS

- Molded type
- High saturation current due to CIP material
- Nature air gap and no acoustic noise
- Different sizes available
- Quantity: 1000pcs

### APPLICATION

- High current DC/DC converter
- LC filter



Model	Inductance (mH)	Inductance Tolerance (%)	DC Current (A)	DC Resistance (mΩ)	Length (mm)	Height (mm)
MD7040-R15N	0.15	±30%	30	55	0.9	1.2
MD7040-R47M	0.47	±20%		28	3.0	3.4
MD7040-R68M	0.68	±20%	16		4.1	4.5
MD7040-1R0M	1.00	±20%	14		6.8	8.0
MD7040-1R5M	1.50	±20%	12	20	10	12
MD7040-2R2M	2.20	±20%	9.0	14	11.5	14
MD7040-4R7M	4.70	±20%	6.0	11	28	32.5
MD7040-6R8M	6.80	±20%	4.5	8.5		50
MD7040-8R2M	8.20	±20%	4.5	8.0	55	
MD7040-100M	10.0	±20%	4.0	7.0		
MD7040-150M	15.0	±20%	3.0	3.5	80	90
MD7040-220M	22.0	±20%	2.5	3.5	120	145
MD7040-330M	33.0	±20%	1.8	3.2	180	210

Operating temperature : -40C ~ +125C

Temperature rise current : The actual value of DC current when the temperature rise is T40C Saturation Current that will cause initial inductance to drop 20% approximately .

