

Flat Wire Molded Inductor Size 4020





- Flat wire coil for low copper losses
- Composite core material allows high saturation currents
- Very low acoustic noise and very low leakage flux noise
- High current capability and handles high transient current spikes
- AEC-Q200 qualified
- Operating temperature -55 to +155 °C (Including self - temperature rise)
- Quantity: 3000pcs

- DC/DC converters for entertainment/navigation systems
- Noise suppression for motors: windshield wipers / power seats / power mirrors / heating and ventilation blowers / HID lighting
- LED drivers

Dimensions: [mm]

Land Pattern: [mm]



Electrical Properties:

	(μH)	$\pm 20\%$	(A)	(A)		(m Ω)
MDTA4020-R10M	0.10	$\pm 20\%$	38.0	13.5	18.0	2.42
MDTA4020-R22M	0.22	$\pm 20\%$	19.5	13.0	16.8	4.60
MDTA4020-R36M	0.36	$\pm 20\%$	17.0	11.0	14.5	6.30
MDTA4020-R40M	0.40	$\pm 20\%$	15.5	10.0	14.0	7.73
MDTA4020-R47M	0.47	$\pm 20\%$	14.5	9.0	12.5	8.58
MDTA4020-R56M	0.56	$\pm 20\%$	14.0	8.5	12.0	9.30
MDTA4020-R60M	0.60	$\pm 20\%$	13.7	8.0	11.7	9.52
MDTA4020-R72M	0.72	$\pm 20\%$	12.0	7.6	10.5	11.6
MDTA4020-1R0M	1.00	$\pm 20\%$	9.6	6.8	9.6	14.6
MDTA4020-1R2M	1.20	$\pm 20\%$	9.0	6.6	9.0	17.9
MDTA4020-1R5M	1.50	$\pm 20\%$	8.0	5.8	7.6	23.5
MDTA4020-1R8M	1.80	$\pm 20\%$	7.5	5.2	7.0	28.0
MDTA4020-2R2M	2.20	$\pm 20\%$	6.5	4.6	5.6	38.7

Saturation Current will cause L to drop approximately 30%

Soldering Reflow:

Preheat condition: 150 ~200°C / 60~120 sec.

Allowed time above 217°C : 60~90 sec.

Max temperature: 260°C.

Max time at max temperature: 10 sec.


Allowed Reflow time: 2x max.

Packaging Information:

Tape Dimension:

Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
MDTA4020	4.5± 0.1	4.5± 0.1	1.5± 0.1	4.0± 0.1	8.0± 0.1	12.0± 0.3	2.3± 0.1	1.75± 0.1	0.35± 0.05

Peel force of top cover tape:



The peel force of top cover tape shall be between 0.1 to 1.3 N

Reel Dimension: [mm]



Packaging Quantity: